

SAFETY DATA SHEET

1. Identification

Product identifier

Product list

Glass Mat Faced Gypsum Panels

Product List A

DensArmor Plus® High Performance Interior Panel
DensArmor Plus® Fireguard® Abuse-Resistant Panels
DensArmor Plus® Fireguard® Impact-Resistant Panels
DensArmor Plus® Fireguard® Interior Panels
DensDeck® Prime Roof Board
DensDeck® Roof Board
DensDeck® Prime Fireguard® Roof Board
DensDeck® Fireguard® Roof Board
DensElement™ Sheathing
DensGlass® Fireguard® Sheathing
DensGlass® Shaftliner
DensGlass® Sheathing
DensShield® Fireguard® Tile Backer
DensShield® Tile Backer
Fire-Rated GreenGlass® Prime Roof Board
Fire-Rated GreenGlass® Sheathing
Fire-Rated GreenGlass® Tile Backer
Fire-Rated GreenGlass® Roof Board
Fire-Rated GreenGlass® Interior Panels
GreenGlass® Prime Roof Board
GreenGlass® Roof Board
GreenGlass® Sheathing
GreenGlass® Tile Backer
GreenGlass® Interior Panels

Product List B

DensArmor Plus® Fireguard C® High-Performance Interior Panels
GreenGlass® Shaftliner

Other means of identification

Product code

GP-71C

Recommended use

Products accommodate a wide range of wall, floor, ceiling and roof applications.

Recommended restrictions

Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company name

Georgia-Pacific Gypsum LLC

Address

133 Peachtree Street, NE
Atlanta, GA 30303

Telephone

Technical Information 800.225.6119
(M)SDS Request 404.652.5119

E-mail

Not available.

Emergency phone number

Chemtrec - Emergency 800.424.9300

2. Hazard(s) identification

Emergency overview

This product is not hazardous in the form in which it is shipped by the manufacturer but may become hazardous by downstream activities such as cutting, sanding, or otherwise working with this product that generate large amount of dusts. Those hazards associated with large amount of dusts are described below.

Physical hazards

Not classified.

Health hazards

Serious eye damage/eye irritation

Category 2B

| | |
|--|---|
| Environmental hazards | Not classified. |
| OSHA defined hazards | Not classified. |
| Label elements | |
| Hazard symbol | None. |
| Signal word | Warning |
| Hazard statement | Causes eye irritation. |
| Precautionary statement | |
| Prevention | Observe good industrial hygiene practices. Wash thoroughly after handling. |
| Response | Wash hands after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Storage | Store away from strong acids. |
| Disposal | Dispose of waste and residues in accordance with local authority requirements. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---------------------------------|--------------------------|------------|----------|
| CALCIUM SULFATE DIHYDRATE | | 10101-41-4 | 60 - 100 |
| VERMICULITE** | | 1318-00-9 | 0 - 7 |
| CONTINUOUS FILAMENT GLASS FIBER | | 65997-17-3 | 1 - 5 |
| CRYSTALLINE SILICA (QUARTZ)* | | 14808-60-7 | 1 - 5 |

Composition comments ** Found in products in List B, Section 16 of this SDS.

Gypsum (calcium sulfate, dihydrate) and vermiculite contain naturally occurring crystalline silica (quartz) which is listed as a lung carcinogen. See Section 8 for exposure information.

*The weight percent for crystalline silica represents total crystalline silica and not the respirable fraction. Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

4. First-aid measures

| | |
|---|---|
| Inhalation | If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | For skin contact, wash immediately with soap and water. Get medical attention if irritation develops and persists. |
| Eye contact | Do not rub the eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Ingestion | Rinse mouth. May result in obstruction and irritation if ingested. Get medical attention. |
| Most important symptoms/effects, acute and delayed | Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

| | |
|--|---|
| Unsuitable extinguishing media | None known. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | Firefighters should wear full protective clothing including self contained breathing apparatus. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | No unusual fire or explosion hazards noted. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Use personal protection recommended in Section 8. Keep unnecessary personnel away. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. |
| Methods and materials for containment and cleaning up | Sweep up or gather material and place in an appropriate container for disposal. Minimize dust generation. Utilize wet methods, if appropriate, to minimize dust. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Keep out of drains, sewers, ditches, and waterways. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Provide appropriate exhaust ventilation at places where dust is formed. Minimize dust generation and accumulation. Do not breathe dust. Do not get this material in contact with eyes. Do not taste or swallow. Avoid prolonged exposure. Observe good industrial hygiene practices. Use only in well-ventilated areas. Wear appropriate NIOSH approved dust mask or filtering facepiece if dust is generated. Do not eat or drink while using the product. Wash hands before eating, drinking, or smoking. |
| Conditions for safe storage, including any incompatibilities | Store level and keep dry. Dewpoint or other conditions causing the presence of moisture can damage the product during storage. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table Z-3: Calculated Time Weighted Average (TWA) (mg/m3)

| Components | Type | Value | Form |
|---|------|------------|-------------|
| CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) | TWA | 4.29 mg/m3 | Total dust. |
| | | 1.43 mg/m3 | Respirable. |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--|------|----------|----------------------|
| CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| VERMICULITE** (CAS 1318-00-9) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |

US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m3, non-standard units

| Components | Type | Value | Form |
|---|------|-------------|----------------------|
| CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4) | TWA | 10 mg/m3 | Inhalable fraction. |
| | | 0.025 mg/m3 | Respirable fraction. |
| CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) | TWA | 0.025 mg/m3 | Respirable fraction. |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|---|------|------------------------|---------------------------|
| CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4) | TWA | 5 mg/m3 | Respirable. |
| CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) | TWA | 10 mg/m3 0.05 mg/m3 | Total Respirable dust. |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Exposure limits for CRYSTALLINE SILICA - The US OSHA exposure limits 8 hour TWA for CRYSTALLINE SILICA (QUARTZ) are calculated from the following equations: $30/(\%SiO_2+2)$ mg/m3 for total dust; and $10/(\%SiO_2+2)$ mg/m3 for the respirable fraction.

*Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

Appropriate engineering controls

Score and snap method recommended. When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Safety glasses or goggles are recommended when using this product. Ensure compliance with OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection.

Skin protection**Hand protection**

For prolonged or repeated skin contact use suitable protective gloves.

Other

Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR 1910.151 (c)).

Respiratory protection

A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards

Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Gypsum boards

Physical state

Solid.

Form

Solid

Color

Facing color varies

Odor

Low odor

Odor threshold

Not available.

pH

6 - 8

Melting point/freezing point

Not applicable.

Initial boiling point and boiling range

Not applicable.

Flash point

Not applicable.

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

| | |
|--------------------------------|-----------------|
| Flammability limit - lower (%) | Not applicable. |
| Flammability limit - upper (%) | Not applicable. |
| Explosive limit - lower (%) | Not applicable. |
| Explosive limit - upper (%) | Not applicable. |

| | |
|------------------|-----------------|
| Vapor pressure | Not applicable. |
| Vapor density | Not applicable. |
| Relative density | Not available. |

Solubility(ies)

Solubility (water) 0.2 % @ 22°C

Partition coefficient (n-octanol/water) Not applicable.

Auto-ignition temperature Not applicable.

Decomposition temperature Not available.

Viscosity Not applicable.

Other information

Flash point class Not flammable

Specific gravity 2.2 - 2.4

10. Stability and reactivity

Reactivity Contact with strong acids produces carbon dioxide.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

Incompatible materials Strong acids.

Hazardous decomposition products May include and are not limited to: calcium oxide and sulfur dioxide.

11. Toxicological information**Information on likely routes of exposure**

Inhalation Inhalation of dusts may cause respiratory irritation.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Dust in the eyes will cause irritation.

Ingestion Not applicable under normal conditions of use. May cause gastrointestinal irritation if ingested.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

Information on toxicological effects**Acute toxicity**

| Product | Species | Test Results |
|--|---------|----------------------|
| Glass Mat Faced Gypsum Panels | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 1731 mg/kg estimated |
| Components | Species | Test Results |
| CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | > 1581 mg/kg |

| | |
|--|---|
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. |
| Serious eye damage/eye irritation | Dust in the eyes will cause irritation. |
| Respiratory or skin sensitization | |
| Respiratory sensitization | Not likely to cause respiratory sensitization. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | Not classified. |
| Carcinogenicity | Not expected to be hazardous by OSHA criteria. |

Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) Known To Be Human Carcinogen.

| | |
|---|---|
| Reproductive toxicity | Not classified. |
| Specific target organ toxicity - single exposure | Not classified. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not classified. |
| Chronic effects | Not hazardous under normal conditions of use. |

12. Ecological information

Ecotoxicity Not considered to be harmful to aquatic life.

| Components | Species | Test Results |
|--|---------|---|
| CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Fish | LC50 | Fathead minnow (<i>Pimephales promelas</i>) > 1970 mg/l, 96 hours |
| CONTINUOUS FILAMENT GLASS FIBER (CAS 65997-17-3) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Fish | LC50 | Zebra danio (<i>Danio rerio</i>) > 1000 mg/l, 96 hours ECHA |
| CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Fish | LC50 | Zebra danio (<i>Danio rerio</i>) > 10000 mg/l, 96 Hours OECD SIDS |

| | |
|--------------------------------------|---|
| Persistence and degradability | No data is available on the degradability of this product. |
| Bioaccumulative potential | No data available. |
| Mobility in soil | No data available. |
| Other adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |

13. Disposal considerations

| | |
|-----------------------------------|---|
| Disposal instructions | Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |

| | |
|--|--|
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. |
| Contaminated packaging | Not available. |

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is not hazardous in the form in which it is sold and shipped by the manufacturer. However, the large amount of dusts generated by downstream activities such as cutting, sanding, or otherwise working with this product is considered hazardous and is regulated under the Hazard Communication Standard 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)

US. Massachusetts RTK - Substance List

CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)
 CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)
 CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)
 CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada | Domestic Substances List (DSL) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|-----------------------------|--|
| Issue date | March-13-2015 |
| Revision date | October-02-2015 |
| Version # | 04 |
| HMIS® ratings | Health: 1 Flammability: 0 Physical hazard: 0 |
| NFPA ratings | Health: 1 Flammability: 0 Instability: 0 |
| Disclaimer | This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete. |
| Revision Information | Product and Company Identification: Product Codes |